



# STREET SCENE EQUIPMENT, INC.

365 McCormick Avenue  
Costa Mesa, CA. 92626  
Phone (714) 426-0590 Fax (714) 426-0591

950-17734  
2004  
FORD F-150  
ELECTRIC MIRRORS  
WITH FACTORY SIGNAL  
& FACTORY HEATED GLASS

## INSTALLATION INSTRUCTIONS

**NOTE:** Please check year, make, and model against application part number. Be sure both mirror heads and mounting plates are left & right side before painting. Parts that have been painted are not eligible for return.

**NOTE:** Check Your Mirror Plugs To Make Sure They Plug Into Your wire harness before painting, If painted warranty will be void.

**NOTE:** Mirrors are designed for specific year vehicles. Although mirror may appear to be the same, the electrical connectors will vary year to year. If your mirror does not plug into your factory wire harness, please check your part number and application guide.

**NOTE:** Do Not Use Loctite On Threads. Warranty Will Be Void If Used

**NOTE:** Do Not Attempt To Remove Glass For Paint Damage Could Occur And Glass Will Break.

**NOTE:** Do Not Over Tighten Nuts, Mounting Brackets Will Crack

**NOTE:** If Painting Mirrors Tape Over Threads To Keep Paint Off

**VERY IMPORTANT !** Read and understand all directions, then check the following parts list before starting installation.

PARTS LIST					
2	Mirror Heads	1	Instruction Sheet	6	6 mm Nuts
2	Mirror Plates	1	Street Scene Decal		

1. Open door and lower windows.
2. Remove door panel by:
  - A - Pry out the plastic trim behind door release handle and remove the bolt located behind it.
  - B - Lift out window control panel. Disconnect wiring from window control panel. Remove the bolt located behind it.
  - C - Remove the speaker grille. Pry gently taking care not to break tabs. Remove the four screws securing speaker. Remove speaker from door and disconnect wire.
  - D - Pry out the two upper white speaker attaching stand offs. These must be re-used so take care when removing.
  - E - Remove the two screws on the bottom side of door panel. Lift door panel up and away from door to remove.
3. Peel off foam installation from corner of door and disconnect mirror wire.
4. Remove mirror mounting nuts. Save for re-use.
5. Grasp mirror and remove with a up / down side to side rocking motion.
6. Remove foam gasket from backside of mirror.
7. Attach mounting plate to mirror with nuts provided, Tighten securely. **DO NOT** over tighten or use loctite on threads. On electric mirrors guide wire plug through center hole in plate. Install gasket removed in step 6 to plate.
8. Install mirror to door, while guiding wires through hole in door and into cab. Secure mirror to door using three nuts from the OEM mirror.
9. Connect wire harness to mirror plug.
10. Install door panel by lining up hooks on door panel with slots in door and sliding panel down.
11. Install all remaining items in reverse order of removal.