



STREET SCENE EQUIPMENT, INC.

365 McCormick Avenue

Costa Mesa, Ca. 92626

Phone (714) 426-0590 Fax (714) 426-0591

**CONNECTING
STREET SCENE
FRONT & REAR FACE
SIGNAL® MIRRORS
1982 - 1993
"S" SERIES**

CONNECTING STREET SCENE SIGNAL® MIRRORS

INSTRUCTIONS FOR PART NUMBERS		
950-15310	950-17320	950-20320
950-15320	950-18320	950-25310

1. Install Street Scene Signal® Mirrors to doors following mirror installation instructions.
2. Before beginning electrical hook-up, check the operation of turn signals in the front and rear of vehicle. If any problems exist, repair before installing Street Scene Signal® Mirrors.
3. If your vehicle does not have any rubber boots on doors you will need to install some or some other device to have Signal® Mirror wires run into vehicle. If you do not use boots, make sure wires do not touch any bare metal. Use rubber grommets. If you are installing our " Street Smart " electric mirror conversion kit grommets are supplied and instruction.
4. Remove the kick panels. Run the **RED / BLACK** wire from the mirror into the door and into the vehicle.
5. Remove lower dash panels. Run the Signal® Mirror wire across dash to beneath the steering column.
6. The vehicles electrical wiring is located beneath the steering column. Locate the solid **LIGHT BLUE** wire in the bundle. Turn the ignition key so that electrical power is on and activate the driver's side turn signal. Probe the wire with a test light to verify that flashing turn signal is present. Label that wire as "**DRIVER SIDE TURN**". Locate the solid **DARK BLUE** wire in the wire bundle. Activate the passenger side turn signal and probe the wire with the test light to verify that flashing turn signal is present. Label that wire as "**PASSENGER SIDE TURN**".
7. Make sure the harness are routed securely under the dash and enough slack is left for splicing. When splicing do not cut any wires. Use the quick splice connectors provided.
8. Splice the **RED** wire from the driver's side harness into the **LIGHT BLUE** wire previously labeled "**DRIVER'S SIDE TURN**".
9. Splice the **RED** wire from the passenger side harness into the **DARK BLUE** wire previously labeled "**PASSENGER SIDE TURN**".
10. Strip and twist together the ends of the **BLACK** wires from each harness. Crimp them together in the supplied ring connector and ground to a suitable nearby location on the metal framework of the vehicle.
11. Activate each turn signal to verify that the Street Scene Signal® Mirrors are working. Replace all of the lower dash panels.