



STREET SCENE EQUIPMENT, INC.

365 McCormick Avenue

Costa Mesa, Ca. 92626

Phone (714) 426-0590 Fax (714) 426-0591

950-61100
 FLIP-UP LICENSE
 PLATE KIT
 ROLLPAN LIGHT KIT

INSTALLATION INSTRUCTIONS

VERY IMPORTANT ! Read and understand all directions and check the following parts list before starting installation.

PARTS LIST					
1	Flip license bracket	1	Instruction Sheet	2	Phillips head Sheet Metal Screws
2	1/4-20 X 3/4" Bolts	2	1/4 - 20 Nyloc Nuts	2	License Plate Retainers
2	Butt connectors	2	1/4" Flat Washers	2	Phillips License Screws
2	# 8 Speed Nuts	1	Lamp Template	1	Roll Pan Light

TOOL LIST	
Drill Motor, Phillips Screwdriver, Safety Glasses, 5/64" drill Bit, 3/8" Ratchet, 3" Extension, 7/16" Wrench	
7/16" Socket, Wire Cutters, File Or Sandpaper, 3/4" Hole Saw, Tape Measure, Crimp Pliers, Saw Blade	

1. Before beginning installation be sure to wear proper eye protection.
2. If roll pan is also being installed, install kit on roll pan prior to installing the roll pan.
3. Find the center of the license bucket in the roll pan by measuring with tape measure and mark center with pencil. Continue the line up and mark the center of the overhead area where license lamp will go.
4. Cut off the bottom of page with lamp mounting template.
5. Tape the template to top of license bucket and center with line drawn in step 3.
6. Drill 5/64" holes to the right and left outside marks at top of roll pan. Using a 3/4" hole saw drill the two inside hole marks. Cut out between holes (shaded area in template). Sand or file hole smooth.
7. Set the flip up bracket on rollpan and center with line marked. Mark mounting holes and drill to 1/4" inch. Before drilling make sure bracket when flipped up will clear the top. Allow for license plate and frame.
8. Connect OEM license light wires to roll pan light provided, Using the red butt connectors. Crimp with crimp pliers, NOTE: It does not matter on wire placement.
9. Install roll pan light from the inside of roll pan. Attach with the # 8 phillips screws from the outside using the # 8 speed nuts to fasten the light in place.
10. Attach flip license plate with 1/4-20 X 3/4" bolts. Use flat washer on back side and tighten nyloc nuts provided snugly. **CAUTION:** Do not overtighten.
11. Install plastic license plate retainers in flip plate. Attach license plate with phillips head screws provided.
12. Test license light operation.

