

STREET SCENE EQUIPMENT, INC.

365 McCormick Avenue Costa Mesa, Ca. 92626 Phone (714) 426-0590 Fax (714) 426-0591

950-61140 **FORD F-150 FLEETSIDE** 1997 - 2003 **TAILGATE** HANDLE RELOCATOR

INSTALLATION INSTRUCTIONS

VERY IMPORTANT! Read and understand all directions and check the following parts list before starting installation.

PARTS LIST					
1	Handle Relocator	1	Instruction Sheet	4	# 8 X 3/4" Washer Head Screws
1	Filler Plate	1	Street Scene Decal		

Ī	TOOL LIST
I	Phillips Screwdriver, Cutting wheel, Die Grinder, Welder (Wire Feed) Tape Measure, Torx Socket Set

- 1. Remove the tailgate from the truck and place face down on saw horses or covered bench.
- 2. Remove inside inspection panel, Disconnect rods from handle, then remove the two mounting bolts and remove handle from tailgate see photo 1, 2, 3.

PHOTO #1 PHOTO #2







3. Using diagram A, cut inner bracing to make room for relocator see photo 4 & 5.

PHOTO #4







4. Using diagram B, cut inspection panel see photo 6 & 7.

PHOTO #6



PHOTO #7



- 5. The inner brace must also be cut out see photo #8.
- 6. Reinstall inspection panel into tailgate and bolt down.

PHOTO #8



7. Mount handle into relocator using factory bolts. See photo 9 & 10.

PHOTO # 9

PHOTO #10



8. Place handle relocator in tailgate and hook up latch rods. See photo # 11

PHOTO #11

9. Using screws provided mount relocator to tailgate. See photo 12 Make sure handle and rods move freely.

PHOTO # 12





- 10. Turn tailgate over face up.
- 11. Remove all paint from original handle hole and approximately 2" around hole. See photo # 13

PHOTO #13



12. Place supplied handle filler plate cover over existing hole and tack weld into place. We recommend a mig (wire feed) welder. **NOTE:** Welding one continuous line will cause tailgate to warp. Tack a small area then let cool and repeat until complete. See photo # 14.

PHOTO #14



13. Grind down the welds and finish off with body filler, block sand, primer and paint. Now your ready to re-install the tailgate back onto the truck.



