



## STREET SCENE EQUIPMENT, INC.

365 McCormick Avenue  
Costa Mesa, CA. 92626  
Phone (714) 426-0590 Fax (714) 426-0591

950-70308  
2013-2015 SCION FR-S/  
SUBARU BRZ  
REAR TRUNK SPOILER  
URETHANE

### INSTALLATION INSTRUCTIONS

**NOTE:** Fit all parts before painting (See Special Instructions For Paint Prep.) Parts that have been installed, prepped, or painted are not returnable.

**VERY IMPORTANT!** Read and understand all directions and check the following parts list before starting installation.

PARTS LIST					
1	Trunk Wing	1	Instruction Sheet	12 FT.	1/2" Two Sided Tape
1	Urethane Prep Sheet	2	Adhesion Promoter		

TOOL LIST	
No tools necessary.	

### NOTE:

Please remove any factory O.E. spoiler/wing prior to installing the Street Scene part.

1. Pre-fit the piece onto the vehicle (**Fig.1**). Once you are assured that you have the correct aero kit, you may proceed. If you don't. Please call Street Scene right away. We highly recommend using masking tape anywhere the aero kit may be touching the vehicle body to prevent scratches during pre-fitment. Perform any sanding, filling, or spacing necessary (before painting) for a clean tight fit. Spending the extra time now will assure you a perfect "factory" Installation.



2. On the back of the trunk wing, there is an indentation. This is where you apply the double sided tape. **(Fig.2)** This surface has to be CLEAN and DRY for the tape to properly adhere. A residual-free cleaner is recommended to prepare the surface. The surface of the vehicle should also be cleaned for proper adhesion. **(Fig.3)** For best results after cleaning, an adhesion promoter such as 3M Part #06396 should be applied to wherever tape is used. We also recommend scuffing the paint where the tape will be adhering for best results. When applying tape, make sure that tape is smooth and wrinkle free. It is best to use 3 to 4 different pieces on long sections rather than 1 piece.



3. After applying tape. Pull back approximately 1 inch of protective covering on tape from each end. Make sure the film is sticking out. Make sure to prepare the surface where you will apply to trunk wing. **(Fig.3)** Place the trunk wing GENTLY on the vehicle and make sure you have it positioned correctly. It is a good idea to have a friend help with this. If adhesion promoter was used you will NOT get a second chance! While holding it in position, pull the tab you created while applying light downward pressure. **(Fig.4)** Continue this while taking care not to tear off the tabs by pulling too hard. After all the film is removed, apply firm pressure all around to insure the tape has bonded properly.

