



## STREET SCENE EQUIPMENT, INC.

365 McCormick Avenue

Costa Mesa, Ca. 92626

Phone (714) 426-0590 Fax (714) 426-0591

950-70503

2002 - 2005

DODGE RAM

ROLL PAN

### INSTALLATION INSTRUCTIONS

**NOTE: Fit all parts before painting ( See special instructions for paint Prep. ) Parts that have been installed, prepped, or painted are not returnable.**

**VERY IMPORTANT !** Read and understand all directions and check the following parts list before starting installation.

### NOTE: FACTORY HITCH MUST BE REMOVED IN ORDER FOR ROLL PAN TO WORK

#### PARTS LIST

1	Roll Pan	1	Instruction Sheet	7	Phillips Head Sheet Metal Screws
1	Crank Hole Cover	1	Street Scene Decal		

#### TOOL LIST

Drill Motor, Phillips Screwdriver, Safety Glasses, 5/32" Drill Bit, Masking Tape, 1 3/8" Hole Saw

1. Before beginning installation be sure to wear proper eye protection.
2. Remove bumper if so equipped.
3. Remove the tailgate from the truck, this is achieved by opening the gate, lifting the limiting cables so the knee action goes up instead of down. Close the tailgate slightly and slide the larger opening in the limiting strap over the retaining pin.
4. At this point close the tailgate to about 85% of it's closed position. CAUTION: Be sure you have a good hold on the gate. The hinge on the passenger side of the vehicle has a slot so the gate will slide up and out in this position. Then move the gate away from the truck and out of the left hinge.
5. Set roll pan into position. Take two small pieces of cardboard and place between roll pan and bed corners to center the roll pan. Fold the cardboard in half if necessary. Align lower edges with corners of bed. Tape roll pan in place.
6. Drill five 5/32" holes in roll pan. One in the center, one at each corner 1 1/2" from ends and one between the center hole and outside holes. Continue to drill through and into bed. Attach to bed with sheet metal screws provided.
7. From inside lower corner lip of roll pan drill into bed corners. Align corners of roll pan and attach with screws provided.
8. If you would like to retain the spare tire you will need to bore a 1 3/8" hole in roll pan where the crank mechanism handle will have to go through. To do this from the back side mark where the crank mechanism handle will have to go through the roll pan. Remove roll pan and drill a hole through at the center point of hole marked. From the front side drill an 1 3/8" hole through using a hole saw. Drill carefully so that the plug provided will snap into hole tight.
9. Paint to match. Follow urethane parts surface preparation procedures. DO NOT forget to paint the plug too.