

STREET SCENE EQUIPMENT, INC.

365 McCormick Avenue Costa Mesa, Ca. 92626 Phone (714) 426-0590 Fax (714) 426-0591

INSTALLATION INSTRUCTIONS

NOTE: Fit all parts before painting (See Special Instructions For Paint Prep.) Parts that have been installed, preped, or painted are not returnable.

NOTE:

THIS FITS THE 6 CYL CAR ONLY

USE P.N. 950-7X756 REAR SPEED GRILLE. INSTALL GRILLE PRIOR TO INSTALLING REAR FASCIA LIP

Check fit all body parts PRIOR to painting. Follow urethane prep instructions before painting. Take your time and pre-fit all pieces so that they will have a tight fit to body.

VERY IMPORTANT ! Read and understand all directions and check the following parts list before starting installation.

PARTS LIST						
1	Rear Fascia Lip Valance				8 FT	1/2" Wide Two Sided Tape
		1	Urethane Prep Sheet		1	Street Scene Decal
		1	Instruction Sheet		3 PKGS	3M Adhesion Promoter
1	Black Out Decal For Rear Fascia Lip Valance					

TOOL LIST

- 1. Set the rear fascia lip to the body to see mounting location. Clean the area where the fascia lip will attach, with a wax & grease remover.
- 2. Set fascia lip on a covered bench or table. Remove all paint from the tape apply edge. Clean the area with a scotch brite pad and wax & gease remover.
- **3.** Wipe area with the adhesion promoter. Apply the tape along the top edge. DO NOT remove tape backing at this time, Lift up the corners of the tape backing at each end.
- 4. Install the "Black Out " decal to recessed area in the center of the fascia lip after painting.
- 5. Set the rear fascia lip into position on the rear of car. With the aid of another person hold into position when you are satisfied with the position, pull the corner of the tape backing and remove the backing while applying pressure over the tape.

04/07/06 SSE 950-70752