



## STREET SCENE EQUIPMENT, INC.

365 McCormick Avenue

Costa Mesa, Ca. 92626

Phone (714) 426-0590 Fax (714) 426-0591

950-72104

CHEVY CK PICK UP  
FIBERGLASS HOOD COWL  
MEDIUM COWL  
WITH BULL NOSE

### INSTALLATION INSTRUCTIONS

**NOTE: Fit all parts before painting ( See special instructions for paint Prep. ) Parts that have been installed, prepped, or painted are not returnable.**

**VERY IMPORTANT !** Read and understand all directions and check the following parts list before starting installation.

PARTS LIST					
1	Hood Scoop	1	Instruction Sheet	1	Fiberglass Paint Prep Sheet
		1	Street Scene Decal	10 FT.	Two Sided 1/2" Wide Tape
4	Washer Head Phillips Sheet Metal Screws				

TOOL LIST	
Masking Tape, Marker, Tape Measure, 5/32" & 3/32" Drill Bits, Drill Motor, Sand Paper	

**The Chevy CK add-on fiberglass hood scoop is self aligning to the contour of hood.**

### PRE FIT BEFORE PAINTING

1. Remove hood pad from under side of hood by prying out the round black plastic fasteners. Save for re-installation.
2. Set the leading ( Front ) edge of scoop on the front lip of hood. Measure to the right and left of scoop to the top ( closes to windshield ). Outside edges of hood. Center scoop on hood. Mark a line ten inches long, each side of the top side of hood scoop. Remove hood scoop. Draw a line 1/2" inch inward ( Toward center ). Flip the hood scoop over and you will notice a one inch wide flange on the top under side. Drill two 5/32" holes in this area in hood. **DOUBLE CHECK** before drilling. Remember **YOU** are responsible for drilling the holes in the correct position. Double / thriple check before drilling.
3. Set the scoop onto hood and observe the side of scoop to hood. Mark the high spots and sand so that the scoop fits tightly against hood.
4. Paint to match follow paint prep instructions.
5. Install the two sided tape along the sides of scoop and place on hood while alligning.
6. Drill four 3/32" holes from the unside of hood through the holes drilled in step two into the fiberglass scoop. Be carefull **NOT** to drill through the top side of hood. Secure with the four screws provided.
7. Install hood pad remove in step one back on hood. You may pruchase new hood pad fastners from local GM dealership of your choice.