

## STREET SCENE EQUIPMENT, INC.

365 McCormick Avenue Costa Mesa, Ca. 92626 Phone (714) 426-0590 Fax (714) 426-0591 950-74590 BLACK SATIN
POWDER COAT
&
950-76590 BLACK CHROME
&
950-77590 SATIN FINISH
&
950-78590 CHROME FINISH
STREET SCENE GRILLE
SHELL W / SPEED
GRILLE INSERTS

## INSTALLATION INSTRUCTIONS

**VERY IMPORTANT!** Read and understand all directions and check the following parts list before starting installation.

## NOTE: THIS GRILLE IS FOR THE GT MODEL ONLY

PARTS LIST						
1	Grille Shell W / Speed Grille Inserts			2	14" Wire Harness Extensions	
2	11" Wire Tie Straps	1	Instruction Sheet	8	Washer Head Phillips Screws # 71834	
1	Care For Grilles	1	Street Scene Emblem			

TOOL LIST
1/8" Drill Bit, # 6 Torx Socket, Panel Removal Tool, Flat Blade Screwdriver, 1/8" Drill Bit, Phillips Screwdriver,
Drill Motor

- 1. Open hood and remove the 6 push in fasteners that secure the plastic header panel cover, by prying up the center pin and then prying up the body. Save fasteners.
- **2.** Reach in and unplug the wire harness connections at the fog lamps in grille.
- **3.** Remove the OEM Grille Shell from the front fascia by depressing the tabs on fascia whilepushing the tab on grille shell in opposite direction.
- **4.** Remove the fog lamps from the grille shell and install into the Street Scene grille shell. Drill an 1/8" hole in center of light mounting. Install light using the screws provided.
- **5.** Connect the harness extensions to the light harness connection. Route to center of vehicle. Use a wire tie on each harness extension to support.
- 6. Install grille shell back into vehicle.
- 7. Install the plastic header panel removed in step 1.

THE SPEED GRILLE™ may be covered by one or more of the following U.S. Patents: D427,119,D425,834,D421,585,D420, 961,D420,960,D420,959, and D420,958 may be covered by one or more pending U.S. Patent applications.