

STREET SCENE EQUIPMENT, INC.

365 McCormick Avenue Costa Mesa, Ca. 92626 Phone (714) 426-0590 Fax (714) 426-0591

INSTALLATION INSTRUCTIONS




VERY IMPORTANT ! Read and understand all directions and check the following parts list before starting installation.

NOTE: CUTTING REQUIRED

PARTS LIST						
1	Speed Grille Insert	1	Instruction Sheet	7	Installation Clips # 71098 3/4" Long	
1	Care For Grilles	1	Street Scene Emblem	4	Installation Clips # 71097 1/2" Long	
	TOOL LIST					
Basic Hand Tools, Cutting Tool, Masking Tape, Black Spray Paint						

1. Remove the OEM grille shell from vehicle by removing the four fasteners across the top and then depressing the tabs on the lower side.

- 2. Set grille shell on a bench and tape off the chrome perimeter. Using a suitable cutting tool remove the horizontal and small vertical bars. Sand smooth to perimeter chrome ring. (CAUTION !!!! DO NOT SAND OR SCRATCH CHROME).
- 3. Mask perimeter chrome ring and paint sanded area with a satin or flat black paint.
- 4. Install Speed Grille insert into opening. Using one 71098 clip 3/4" long attach the top center. Attach the bottom side using remaining six clips. Attach the side to grille shell using two 71097 clips 1/2" long on each side.
- 5. Re-install grille shell into vehicle.



TYPICAL CLIP INSTALLATION

THE SPEED GRILLE™ may be covered by one or more of the following U.S. Patents: D427,119,D425,834,D421,585,D420, 961,D420,960,D420,959, and D420,958 may be covered by one or more pending U.S. Patent applications.