



STREET SCENE EQUIPMENT, INC.

365 McCormick Avenue

Costa Mesa, CA. 92626

Phone (714) 426-0590 Fax (714) 426-0591

INSTALLATION INSTRUCTIONS

950-77500 SATIN FINISH

&

950-78500 CHROME FINISH

SPEED GRILLE

1994 - 2001

DODGE RAM

MAIN GRILLE

VERY IMPORTANT ! Read and understand all directions and check the following parts list before starting installation.

NOTE: (No Drilling Is Required But Removing The Stock Grille Is Required.)


PARTS LIST

4	Speed Grille Section	1	Instruction Sheet	24	Attaching Clips # 71097
		1	Street Scene Emblem		

TOOL LIST

Safety Glasses, 8 MM Socket, Ratchet, Extension, Grinder, Drill, File Or Other Tool To Remove The Plastic rivets That Retain The Stock " Honey Comb " Grille.

1. Before beginning installation be sure to wear proper eye protection.
2. Remove the grille shell from the vehicle. Open the hood and remove the six 8mm nuts that secure the grille shell across the top to the hood, the two 8mm bolts on each side of the grille, and the single 8mm bolt at the bottom of the grille just above the hood safety latch. Save the fasteners for reinstallation. Leave the metal tube grille support frame in place.
3. To remove the stock mesh grille, lay grille shell face down on a surface that won't damage it (cloth, newspapers, ect.) Remove the ends of the plastic rivets that retain the mesh grille by grinding or filing, then remove the stock grille.
4. Each Speed Grille section is labeled for each opening. Install them one at a time from the front, then secure each section with six clips. The clips install from back of the grille with the raised side of the clips facing to the inside of the grille opening. This is necessary for the clips to clear the vertical lip on back edge of the grille shell. Install each section individually, attaching with three clips equally spaced on the bottom first, then install the top three clips.
5. Make sure the Speed Grille section are properly aligned and securely fastened, then reinstall the grille shell on the vehicle with the original fasteners, Refer to your owners manual for proper torque specifications.



THE SPEED GRILLE™ may be covered by one or more of the following U.S. Patents: D427,119,D425,834,D421,585,D420,961,D420,960,D420,959, and D420,958 may be covered by one or more pending U.S. Patent applications.

6/11/01 SSE 950-77500 & 950-78500