STREET SCENE EQUIPMENT,INC.

365 McCormick Avenue
Costa Mesa, Ca. 92626
Phone (714) 426-0590   Fax (714) 426-0591

INSTALLATION INSTRUCTIONS

VERY IMPORTANT ! Read and understand all directions and check the following parts list before starting installation.

PARTS LIST

1	Upper Grille Insert	1	Instruction Sheet	1	Center RT Grille Insert
1	Lower Grille Insert	1	Street Scene Emblem	1	Center LT Grille Insert
1	Care For Grilles			36	Installation Clips # 71098

TOOL LIST

Flat Blade Screwdriver, Phillips Screwdriver, #30 Torx Socket, Ratchet, Panel Removal Tool

1. Remove the eleven fasteners that secure the panel between the grille and core support by removing the center phillips head screw and then prying out the body. Remove panel.

2. Remove the push in fasteners attaching the rubber air shield to the grille at each end.

3. Reach in behind the front grille and pry off the four silver color clips connecting the grille shell to the fascia.

4. Remove the four # 30 Torx fasteners across the top of grille and remove grille by pushing it forward to release it from the tabs on the bumper cover.

5. Set the grille shell on a protective coverd table or bench.

6. Remove the Speed Grille inserts from the bags, each Speed Grille section is marked for it's location.

7. Install the Speed Grilles into the openings in the grille shell, the shorter side of each grille will face up.

8. From the back side clip each Speed Grille to the grille shell. Look at the drawing below as a referance on installing clips. Use six clips on each center Speed Grille section. Three on the top side and three on the bottom side. On the upper and lower Speed Grilles, Use twelve clips each six on the top and six on the bottom.

9. Install Grille Shell back on vehicle by first inserting the bottom of grille into the tabs on the bumper cover and then installing the fasteners removed in step one and two.