



STREET SCENE EQUIPMENT, INC.

365 McCormick Avenue

Costa Mesa, Ca. 92626

Phone (714) 426-0590 Fax (714) 426-0591

INSTALLATION INSTRUCTIONS

950-77992 SATIN FINISH

&

950-78992 CHROME FINISH

2005

NISSAN ALTIMA

SPEED GRILLE INSERT

VERY IMPORTANT ! Read and understand all directions and check the following parts list before starting installation.

PARTS LIST

1	Speed Grille Insert	1	Instruction Sheet	1 FT.	2" Wide Two Sided Tape
6	11" Cable Ties	1	Street Scene Emblem	1	Care For Grilles

TOOL LIST

1. Open hood and remove the four fasteners across the top of grille shell. Pull and remove grille shell.
2. Set the grille shell on a protective covered table or bench face down. Use a flat blade screwdriver and depress the tabs and remove the Nissan Logo.
3. Below you will see the photo of the grille shell drill 1/4" holes as indicated in photo.

PHOTO



4. Set the Speed Grille insert on the top of grille shell. Use the ladder ties supplied and insert tie around the " Loop " in Speed Grille and thru the holes drilled. Install all ties and pull tight. Additional ties are provided if you would like to add more.
5. If you would like to retain the Nissan logo trim off the protruding tabs on the back side of logo. Install the two sided tape supplied to the back side of logo. Trim of excess tape remove the backing and set the Nissan logo on the Speed Grille over the silhouette of logo on grille shell.
6. Install the Grille Shell back on vehicle.

THE SPEED GRILLE™ may be covered by one or more of the following U.S. Patents: D427,119,D425,834,D421,585,D420,961,D420,960,D420,959, and D420,958 may be covered by one or more pending U.S. Patent applications.

08/02/05 SSE 950-77992 & 950-78992