



STREET SCENE EQUIPMENT, INC.

365 McCormick Avenue
Costa Mesa, Ca. 92626

Phone (714) 426-0590 Fax (714) 426-0591

950-76777 BLACK CHROME
950-77777 SATIN FINISH
950-78777 CHROME FINISH
950-78777 BLK PDR COAT
09-'13 LARIAT/KING RANCH
SPEED GRILLE INSERTS

INSTALLATION INSTRUCTIONS

NOTE: WILL NOT FIT XL, STX, XLT, AND FX4

VERY IMPORTANT! Read and understand all directions and check the following parts list before starting installation.

PARTS LIST			
1	Top Speed Grille Insert	1	Instruction Sheet
1	RT Center Speed Grille Insert	1	Care For Grilles
1	LT Center Speed Grille Insert	25	Installation Clips # 71096
1	Bottom Speed Grille Insert	4	11" Tie Straps
1	RT Side Speed Grille Insert		
1	LT Side Speed Grille Insert		

TOOL LIST
10 MM Socket, Ratchet, Extension, Flat Blade Screwdriver, Side Cut Pliers, Snap Ring Pliers

1. Open hood.
2. Remove the six 10 MM head nuts along the top side of the grille shell at hood line.
3. Remove the 10 MM head nuts at the right and left lower corners of grille shell, where the shell attaches to the vertical metal brackets.
4. Remove grille shell by lifting up to unsnap the metal fasteners where the grille shell meets the hood.
5. Set the grille shell on a protective covered bench or table. The four horizontal sections of Speed Grille will be attached to the grille shell using the clips provided the longer (straight side) of clips, faces the Speed Grille inserts.
6. Set each Speed Grille sections into it's appropriate opening. Secure to grille shell using the clips provided. Study the photo below carefully and place the clips in the locations shown. Using a flat blade screwdriver or snap ring pliers, spread open the clips when installing.



THE SPEED GRILLE™ may be covered by one or more of the following U.S. Patents: D427,119,D425,834,D421,585,D420,961,D420,960,D420,959, and D420,958 may be covered by one or more pending U.S. Patent applications.

7. Install the side (Vertical) Speed Grille into there locations. Secure to grille shell using two tie straps

