

STREET SCENE EQUIPMENT, INC.

365 McCormick Avenue Costa Mesa, Ca. 92626 Phone (714) 426-0590 Fax (714) 426-0591 950-77872 SATIN FINISH
&
950-78872 CHROME FINISH
2004 - 2005
SCION XB
CENTER & LOWER VALANCE
SPEED GRILLES

INSTALLATION INSTRUCTIONS

VERY IMPORTANT! Read and understand all directions and check the following parts list before starting installation.

PARTS LIST					
1	Center Grille Insert	1	Instruction Sheet	5	Installation Clips # 71098 3/4" Long
1	Lower Grille Insert	1	Street Scene Emblem	15	Installation Clips # 71099 1" Long
1	Care For Grilles				

TOOL LIST
10MM Socket, Extension, Ratchet, Flat Blade Screwdriver

Remove the front fascia from vehicle

- 1. Open hood.
- 2. Remove the three plastic push in fasteners along the top of the upper body grille by prying up the center and then prying out the body using a small flat blade screwdriver. Remove grille. Remove the push in fasteners on the bottom of grille in the same manner.
- 3. Remove the 10MM head bolt in each of the wheel wells where the front fascia meets the front fenders.
- 4. Raise front of vehicle and remove the eight 10MM head bolts securing the bottom of fascia.
- **5.** Remove the two 10MM head bolts on the top side of fascia.
- **6.** With the help of another person remove the fascia, the fascia must be un-snapped at the right and left upper corners by pulling lightly.
- 7. Set the fascia on a covered table or bench face down.
- 8. With a small flat screwdriver pry the fastening points and remove the plastic grilles.
- 9. Install the lower Speed Grille (Taller Grille) into the opening from the front side. Attach from the back side using five 71099 (1" Long Clips) across the top and five 71099 clips (1" Long Clips) along the bottom. Install one clip at each end, one in the center and the remaining two centered between. Refer to illustration for clipping procedure.
- 10. Install the Center Speed Grille (Shorter Grille) into the opening from the back side. Attach using the five 71098 (3/4" Long) clips across the top and five 71099 (1" Long) clips across the bottom. Install one clip at each end, one in center and the remaining two centered between.
- 11. Install fascia in reverse order of removal. Install top grille.

ILLUSTRATION

