



STREET SCENE EQUIPMENT, INC.

365 McCormick Avenue

Costa Mesa, Ca. 92626

Phone (714) 426-0590 Fax (714) 426-0591

950-70202

HOOD COWL

94 - 04 " S " SERIES

INSTALLATION INSTRUCTIONS

VERY IMPORTANT ! Read and understand all directions and check the following parts list before starting installation.

Drilling Necessary

PARTS LIST					
1	Hood Cowl	1	Instruction Sheet	2	Phillips head Sheet Metal Screws
		1	Street Scene Decal		

TOOL LIST	
Drill Motor, Phillips Screwdriver, Safety Glasses, 1/8" Drill Bit, Masking Tape, 13 mm Socket, 7 mm Socket, 3/8" Ratchet, 3" Extension.	

1. Before beginning installation be sure to wear proper eye protection.
2. Remove the wiper arm assemblies by lifting up the black plastic covers from the wiper arm bases. Remove the 13 mm nuts securing the wiper arms.
3. Open hood. Remove the 7 mm head screws securing the right and left corners of the hood seal to the fire wall. Remove the hood seal by gently pulling from left to right.
4. Close hood to latch position.
5. Remove the factory hood cowl (3 Pieces). This is achieved by removing the 7 mm head screws at each end and lifting the corners out and away. The center portion is attached with either four phillips head or 7 mm head screws or a combo of both. Remove screws and lift hood cowl up and back towards windshield
6. Caution must be taken when installing the new hood cowl. Tape upper edge of hood with masking tape to protect the hood and hood cowl when installing. A second person will aid in installation of the hood cowl.
7. With hood open to " latch " position, slide the passenger side of hood cowl under the hood and into wiper arm stud, taking care not to scratch the hood. Ease the drivers side of the hood cowl back towards the windshield and slide over wiper stud.
8. Close hood tight and tape the hood cowl into position.
9. Open the hood to it's full extension. Drill a 1/8" hole through the hood cowl and into the sheet metal at each side where marked and secure it with the fasteners provided.
10. Re-install hood seal to firewall.
11. Paint to match. Follow fiberglass parts surface preparation procedures.